

# TERAFLEX

INSTALLATION GUIDE

## Installation Guide for the Rear Adjustable Track Bar

Part #001744000 (TBART)



*Components:*

- 1 Adjustable rear track bar
- 2 12mm bolts
- 2 12mm nuts
- 2 Flat washers
- 2 Lock washers

Fits TJ Wranglers ('97-newer) with minimum 3" lift, and requires use of a TeraFlex rear track bar bracket or equivalent.

**Instructions:**

1. Disconnect stock track bar from upper and lower track bar mounts.
2. Connect the frame end of the adjustable rear track bar first using the hardware included. The frame end is not adjustable.
3. Connect the lower end of the adjustable rear track bar to the rear track bar bracket using the included hardware.
4. Torque bolts to 50 ft. lbs.

**Note:** the gold colored adjustable end is the axle end. Length must be adjusted to center the rear axle.

# TERAFLEX

INSTALLATION GUIDE

## Installation Guide for the Rear Adjustable Track Bar

Part #001744000 (TBART)



*Components:*

- 1 Adjustable rear track bar
- 2 12mm bolts
- 2 12mm nuts
- 2 Flat washers
- 2 Lock washers

Fits TJ Wranglers ('97-newer) with minimum 3" lift, and requires use of a TeraFlex rear track bar bracket or equivalent.

**Instructions:**

1. Disconnect stock track bar from upper and lower track bar mounts.
2. Connect the frame end of the adjustable rear track bar first using the hardware included. The frame end is not adjustable.
3. Connect the lower end of the adjustable rear track bar to the rear track bar bracket using the included hardware.
4. Torque bolts to 50 ft. lbs.

**Note:** the gold colored adjustable end is the axle end. Length must be adjusted to center the rear axle.