

TeraFlex HD ball joints are engineered to handle the increased load caused by oversized tires and offset wheels. The upper ball joint incorporates hard sintered wear bushings to handle extreme side load demands with out failure and includes an easy top access grease port for simple maintenance.

The lower ball joint features a threaded top cap for precise and accurate preload when assembled as well as future adjustments by the end consumer. The advanced grease system allows grease servicing to be performed without axle shaft removal, even with larger RCV shafts. A machined grease passage in the lower joint housing assembly provides lubrication access without affecting the ball joint load surface. The lower ball joint also eliminates the nylon ball socket wear sleeve that is prone to failure.

These ball joints fit 2007-2011 and most 2013 IK Wrangler Dana 30 and Dana 44 syles. These ball joints fit 2007-2011 and most 2013 JK Wrangler Dana 30 and Dana 44 axles.

BALL JOINT FEATURES

- Hard sintered wear bushings handle side load demands without failure
- 4140 chromoly Ball/stud

- 4140 chromoly Ball/stud
 1045 carbon steel housing
 Magnesium Phosphate anti-corrosion coating
 Abrasion resistant CR Neoprene boot locked into position with spring steel ring
 Factory style castle nut & pin (upper joint)
 Top access grease fitting (upper joint)
 Factory style serrated flanged castle nut & pin (lower joint)
 Adjustable preload end cap with set screws (lower joint)
 Lateral greasing access for easy on the Jeep servicing (lower joint)

- Lateral greasing access for easy on the Jeep servicing (lower joint)
- 100% sealed assembly with o-ring
- · Lifetime Warranty

Note: Fits 2007-2011 and most 2012 JK Wrangler Dana 30 & Dana 44 axles. Late 2012 and newer JKs can modify the outer shaft ears to work with these ball joints. We recommend ball joints without knurls as they will not score the inner knuckle and open up the bore. We also offer ball joint with knurls for ball joints that have a loose press fit in the inner knuckle due to repeated ball joint replacement or if knurled ball joints have been installed previously

APPLICATIONS AND PRICING

JK Ball Joint Upper & Lower Kit - w/out knurl	3440000
JK Ball Joint Upper & Lower Kit - w/ knurl	3440020
JK Ball Joint Upper & Lower Set of 4 - w/out knurl	3442002
JK Ball Joint Upper & Lower Set of 4 - w/ knurl	3442022
Dana 60 Ball Joint Upper & Lower Kit - w/out knurl	3600000

Dana 60 Ball Joint Upper & Lower Kit - w/ knurl Dana 60 Ball Joint Upper & Lower Set of 4 - w/out knurl 3602002 Dana 60 Ball Joint Upper & Lower Set of 4 - w/ knurl

Install Time: 4 hours

Ball Joint Preload Adjustment Tool

1344000