



3" Bull Bar

Part No. B0025S/B



Fits: **2011-Current**


Jeep Grand Cherokee



REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT.




READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.



DO NOT OVER TORQUE. STANDARD OPERATING LOAD FOR TIGHTEN BODY MOUNT NUTS & BOLTS VARIES FROM 45 TO 65 FOOT POUND.



30-60 min



Cutting Not Required



Drilling Not Required



support@trailfx.com




1 866 638 4870



POLISHED STAINLESS STEEL – LIMITED LIFETIME
POWDER COATED BLACK – 3 YEARS

PARTS LIST:

Qty	Part Description	Qty	Part Description
1	Bull Bar	6	12mm Lock Washers
1	Passenger/Right Mounting Bracket	6	12mm Nuts
1	Driver/Left Mounting Bracket	2	10mm T-Bolt
1	Driver/Left Support Bracket	2	10mm x 30mm Hex Bolts
1	Passenger/Right Support Bracket	4	12mm Flat Washers
6	12mm x 30mm Hex Bolts	4	12mm Lock Washers
6	12mm Flat Washers	2	12mm Nuts



INSTALLATION PROCEDURE:

1. It may be necessary to remove the front license plate and bracket. Remove license plate from bracket. Using a 3/16" drill bit, drill out the two pop rivets that hold the bracket to the bumper.
2. Remove tow hooks by removing the front bolt and rear bolt those threads into the side of the tow hooks. Tow hooks will not be reinstalled.
3. Attach Bull Bar to brackets using 12mm fasteners. Level and adjust bull bar as desired. Torque 12mm fasteners **SEE FIGURE 1.**

- (1) 10mm Hex Bolt
- (1) 10mm Flat Washer

- (1) 10mm T-Bolt
- (1) 10mm Flat Washer
- (1) 10mm Lock Washer
- (1) 10mm Nut

FIG 1



- (1) 10mm Hex Bolt
- (1) 10mm Flat Washer
- (1) 10mm Lock Washer
- (1) 10mm Nut

- (1) 12 X 30mm Hex Bolt
- (1) 12mm Flat Washer
- (1) 12mm Lock Washer
- (1) 12mm Nut

- (1) 10mm Hex Bolt
- (1) 10mm Flat Washer
- (1) 10mm Lock Washer
- (1) 10mm Nut

FIG 2A

FIG 2B



Installation Complete



PRODUCT CARE

- Periodically check the product to ensure all fasteners are tight and components are intact.
- Regular waxing is recommended to protect the finish of the product.
- **Use ONLY Non-Abrasive automotive wax.** Use of any soap, polish or wax that contains an abrasive is detrimental and can scratch the finish leading to corrosion.
- Aluminum polish may be used to polish small scratches and scuffs for **Stainless Steel finish.**
- Mild soap may be used to clean the product for both **Stainless Steel and Black finish.**

FAQ'S

1. Hardware's are not of correct size.

In GMC / Chevrolet truck model 2006 & up, customer needs to reuse the factory body bolts to install the bracket. If your vehicle is not GMC / Chevrolet 2006 & up, ensure that holes are not partially covered with any plastic grommet or rust? If it is, remove the plastic grommet & rust from the thread holes & re-try the installation.

2. Mounting Bracket are not getting Installed properly.

In some cases Illustration images shown in Installation manual may not be the exactly same as per actual vehicle images ,also if Driver / Passenger side mounting brackets are very identical in the design, suggest referring Parts Identification guide to avoid fitment issue.

3. Products are thumping / rattling after installation.

Ensure that all required mounting brackets / hardware's are installed & tighten correctly. Suggest using white lithium / regular grease between the metal to metal contact surfaces.

4. Side Bar is not aligning with vehicle / Step Pads are not aligning with vehicle doors.

Side bar may be interchanged or mounting brackets are not installed at the correct position in the vehicle. Refer Parts identification guide.

5. Missing / Excess Hardware.

Recheck hardware count as per the part list.

6. Product not installing properly.

Ensure make model year, cab length and bed size of your vehicle is listed in the application. All installation steps are followed correctly.



SIDE BARS



ROCKER GUARD



HEADACHE RACKS



RUNNING BOARDS

Keystone Automotive Operations Inc. (KAO) warrants this product to be free of defects in material and workmanship at the time of purchase by the original retail consumer. KAO disclaims any other warranties, express or implied, including the warranty of fitness for a particular purpose or an intended use. If the product is found to be defective, KAO may replace or repair the product at our option, when the product is returned prepaid, with proof of purchase. Alteration to, improper installation, or misuse of this product voids the warranty. KAO's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for any incidental or consequential loss or damage.