



Spare Tire Carrier Mount


Part: J035T



Fit: 2007-Current Jeep Wrangler JK



60-180 min



Cutting Not Required




Drilling Not Required



REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT.



READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.



PLEASE USE SAFETY GLASSES & ENSURE TO BLOCK VEHICLE MOVEMENT DURING INSTALLATION PROCESS

PARTS LIST:

Qty	Part Description	Qty	Part Description
4	M8 x 55mm Hex Bolts	4	M8 Lock Washers
2	M6 x 15mm Screws	2	M6 Lock Washers
2	M5 x 38mm Flat Screws	2	M6 Nuts
4	M8 x 20mm x1.8mm Flat Washers	1	M18 x 50mm x 2.6mm Washer
2	M6 x 12mm x 1mm Flat washers		

Step 1: Remove your 3rd brake light from its housing by removing the four screws on the back of it. Follow the wiring and disconnect at plug. Keep the light and screws separately to use later.

Step 2: Remove the factory tire carrier from the tail gate. Keep bolts separately to use later.

Step 3: Keep the tire that you are going to be using flat on the ground, keeping outside of the tire facing down. Adjust spare tire carrier base on tire with the tube portion going through the centre of the wheel. While pushing the tire carrier down (making it even the tire) lay the brake light bracket on the tire carrier between the two flanges. Put the light bracket so the top of it where the light lens will be placed is just above the tire.

Note: If your vehicle is equipped with a 9" x 5" exhaust vent minor trimming will be necessary.

Loosely attach the tire carrier to the back of the jeep and mark where the vent will need to be trimmed. Remove tire carrier and then proceed to carefully trim the edge of the vent.

Step 4: Plug the light wire back into the brake light. Attach the brake light to the brake light bracket with the two supplied tapping screws in the top two hole locations and use two of the original screws you removed in step 1 for the bottom tow hole locations.

Step 6: Install the tire stop bars on the outside holes on the tire carrier. The long end of the bars goes toward the top. Mount each bar using the included 8x55mm bolts, flat washers secure tightly.

Step 7: Adjust your spare tire onto the centre tube of the tire carrier. Place tire hold-down bracket over tube in tire carrier and line up the top two points in two lug holes in the wheel and one in the bottom. Thread the lock down tire handle into the tire carrier. Tighten the handle completely. The tire should be snug against the tire stop bars. Make sure all hardware is tight and the brake light is operational.



Installation Completed