ITEM # 90660
LED WARNING MODULE

Technical Specification
12V DC Input
2 Outputs
10 Amps / Output

Instruction	
Black Wire	Ground
Red Wire	To + VDC
White Wire	Simultaneous or Alternating Flash: - Group 1: "Connect White to Red" will Flash Together - Group 2: "Disconnect White to Red" will Flash Together - Group 1 will Alternate with Group 2 Heads
Yellow Wire	For Synchronization & Flash Patterns: - Connect Yellow Wire of All Heads Together for Synchronization - All Heads Must be Set at the Same Pattern
Switch Pattern	Momentarily Apply VDC to Yellow Wire Once
Reset	Momentarily Apply VD to Yellow Wire for Seven Seconds

Warning: It's Not Necessary to Use Both Outputs If the Total Current Draw is Less Than 10 Amps or You Do Not Want to Alternate the Lights

Flash Pattern					
1	Random	9	Quadruple Alternate	17	Speed Up
2	Steady	10	Quadruple Synchronization	18	Flash Alternate Ver.2
3	Flash Alternate	11	Quintuple Alternate	19	Flash Synchronization Ver.2
4	Flash Synchronization	12	Quintuple Synchronization	20	Sequential
5	Single Alternate	13	Octuple Alternate	21	Sequential Ver.2
6	Single Synchronization	14	Octuple Synchronization	22	Quadruple Alternate + Octuple Synchronization
7	Double Alternate	15	Triple Fast + Triple Slow Alternate	23	Random Ver.2
8	Double Synchronization	16	Triple Fast + Triple Slow Synchronization	24	Slow Down + Single Alternate

When it comes to quality semi truck accessory lighting, United Pacific is the brand you can depend on.