

SAFETY DATA SHEET

Revision Date: 09/05/2017

Print Date: 4/3/2018 SDS Number: 000000135961

Version: 1.3

Valvoline[™] VR1 Racing[™] SAE 20W-50 Synthetic Racing Oil

679082

29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

Product identifier

Trade name

Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Mineral Oil		Asp. Tox. 1; H304	5.70
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	1.14

Version: 1.3



Revision Date: 09/05/2017

Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil

679082

General advice	:	No hazards which require special first aid measures.
If inhaled	:	If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye.
If swallowed	:	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)
Notes to physician	:	No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
------------------------------	--



Version: 1.3

Revision Date: 09/05/2017

Print Date: 4/3/2018 SDS Number: 000000135961

Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil

SAFETY DATA SHEET

679082

Specific hazards during firefighting	Do not a courses	allow run-off from fire fighting to enter drains or water
Hazardous combustion products	Hydroca Carbon	
Specific extinguishing methods		
	Product	is compatible with standard fire-fighting agents.
Further information	Standa	d procedure for chemical fires.
Special protective equipment for firefighters	In the e	vent of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Materials to avoid	: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters					
Components	CAS-No.	Value type	Control	Basis	

	Valvoline	
TM		

SAFETY DATA SHEET	Revision Date: 09/05/2017
	Print Date: 4/3/2018
	SDS Number: 000000135961
Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil	Version: 1.3
679082	

Page: 4

		(Form of exposure)	parameters / Permissible concentration	
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.			
Mineral Oil				
Engineering measures	General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.			
Personal protective equipment Respiratory protection :		espiratory protective equipment normally		
Eye protection :		under normal conditions of use. Wear splash- oggles if material could be misted or splashed		
Skin and body protection :	Wear resistar supplier). Wear as appr Safety shoes	it gloves (consult your safety equipment opriate:		
Hygiene measures :	General indus	strial hygiene practice.		

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	liquid
----------------	---	--------

Odour : No data available



Valvoline[™] VR1 Racing[™] SAE 20W-50 Synthetic Racing Oil

Page: 5

SAFETY DATA SHEET

Revision Date: 09/05/2017

Print Date: 4/3/2018

SDS Number: 000000135961

Version: 1.3

679082

Odour Threshold	: No data available	
рН	: No data available	
Melting point/freezing point	: No data available	
Boiling point/boiling range	: 626 °F / 330 °C (1,013.333333 hPa) Calculated Phase Transition Liquid/Ga	
Flash point	: > 390 °F / > 199 °C Method: Cleveland open cup	15
Evaporation rate	: No data available	
Flammability (solid, gas)	: No data available	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: 1.33333333 hPa (20 °C) Calculated Vapor Pressure	
Relative vapour density	: No data available	
Relative density	: 0.854	
Density	: 0.861 g/cm3	
Density Solubility(ies) Water solubility	: 0.861 g/cm3: No data available	
Solubility(ies)	-	
Solubility(ies) Water solubility	: No data available	
Solubility(ies) Water solubility Solubility in other solvents Partition coefficient: n-	No data availableNo data available	
Solubility(ies) Water solubility Solubility in other solvents Partition coefficient: n- octanol/water	No data availableNo data available	
Solubility(ies) Water solubility Solubility in other solvents Partition coefficient: n- octanol/water	 No data available No data available No data available 	
Solubility(ies) Water solubility Solubility in other solvents Partition coefficient: n- octanol/water Thermal decomposition Viscosity	 No data available No data available No data available No data available 	

SECTION 10. STABILITY AND REACTIVITY



Page: 6

Version: 1.3

SAFETY DATA SHEET

Print Date: 4/3/2018 SDS Number: 000000135961

Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil

679082

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Product will not undergo hazardous polymerization.
Conditions to avoid	:	None known.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products		carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Inhalation
exposure		Skin contact
		Eye Contact
		Ingestion

Acute toxicity

Not classified based on available information. <u>Components:</u> Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity

: LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information. <u>Components:</u> Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information. Product: Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.





Revision Date: 09/05/2017

Print Date: 4/3/2018 SDS Number: 000000135961

Valvoline[™] VR1 Racing[™] SAE 20W-50 Synthetic Racing Oil

SAFETY DATA SHEET

Version: 1.3

679082

Respiratory sensitisation: Not classified based on available information. Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. **Reproductive toxicity** Not classified based on available information. STOT - single exposure Not classified based on available information. STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information. Components: Mineral Oil: May be fatal if swallowed and enters airways.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways.

Further information <u>Product:</u> Remarks: No data available

Carcinogenicity: IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.
<u>Components:</u> Distillates (Petroleum), Hydrot Toxicity to fish	reated Heavy Paraffinic: : LL50 (Fish): > 100 mg/l



Page: 8

Revision Date: 09/05/2017

Print Date: 4/3/2018

SDS Number: 000000135961 Version: 1.3

Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil

679082

SAFETY DATA SHEET

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Aquatic invertebrates): 10 mg/l
Persistence and degradabilit No data available Bioaccumulative potential No data available Mobility in soil No data available Other adverse effects No data available Product:	-	
Additional ecological information	:	No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
General advice	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous	goods
	-



SAFETY DATA SHEET	Revision Date: 09/05/2017
	Print Date: 4/3/2018
	SDS Number: 000000135961
Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil	Version: 1.3
679082	

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity



SAFETY DATA SHEET	Revision Date: 09/05/2017
	Print Date: 4/3/2018
	SDS Number: 000000135961
Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil	Version: 1.3
679082	

Components		CAS-No.		onent RQ	Calculated product R
ZINC		7440-66-6		lbs) 000	(lbs)
*: Calculated RQ exceeds re	easo			000	
SARA 304 Extremely Haza	rdo	us Substances Repo	ortable C		
This material does not conta	in a	ny components with a	section	304 EHS	RQ.
SARA 311/312 Hazards		: No SARA Hazards			
SARA 313		Zinc 0,0,0',0'-		2215-35-	2 0.61 %
		tetrakis(1,3-dimeth bis(phosphorodithic		2210-30-	2 0.01 %
		ZINC DIALKYL DITHIOPHOSPHA	TE	68649-42	2-3 0.47 %
		PHOSPHORODITH ACID, MIXED 0,0- BIS(1,3-DIMETHYI AND ISO-PR) EST ZINC SALTS	_BUTYL	84605-29	9-8 0.36 %
California Prop 65			to cause		emicals known to the rth defects, or other
The components of this pr		ct are reported in th	e follow		
DSL		: All components of t	ins prod	uct are on	the Canadian DSL
AICS		: Not in compliance	with the i	inventory	
ENCS		: On the inventory, o	r in com	pliance wit	h the inventory
KECI		: On the inventory, o	r in com	pliance wit	h the inventory
PICCS		: Not in compliance	with the i	inventory	
IECSC		: On the inventory, o	r in com	pliance wit	h the inventory
TSCA		: On TSCA Inventory	ý		


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 09/05/2017
	Print Date: 4/3/2018
	SDS Number: 000000135961
Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil	Version: 1.3
679082	

Further information

Revision Date: 09/05/2017



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

- CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
- FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.



SAFETY DATA SHEET	Revision Date: 09/05/2017
	Print Date: 4/3/2018
	SDS Number: 000000135961
Valvoline™ VR1 Racing™ SAE 20W-50 Synthetic Racing Oil	Version: 1.3
679082	

SECTION 4. FIRST AID MEASURES

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization" IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent , Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System