

SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 4/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.5
804751	

# 29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

# **Product identifier**

Trade name

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

# SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Skin sensitization	: Category 1
GHS label elements Hazard pictograms	
Signal Word Hazard Statements	<ul><li>: Warning</li><li>: May cause an allergic skin reaction.</li></ul>
Precautionary Statements	<ul> <li>Prevention: Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing before reuse. Disposal: Dispose of contents/ container to an approved waste disposal</li> </ul>



SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 4/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.5
804751	

plant.

# Other hazards

None known.

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

# Hazardous components

nazaruous components			
Chemical name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	67.0534
Acetamide, 2-hydroxy-, N,N- dicoco alkyl derivs.	866259-61-2	Skin Sens. 1; H317	0.999
C14-C18 alpha-olefin epoxide, reaction products with boric acid		Skin Sens. 1; H317	0.1189

# **SECTION 4. FIRST AID MEASURES**

General advice	<ul> <li>Move out of dangerous area.</li> <li>Show this safety data sheet to the doctor in attendance.</li> <li>Do not leave the victim unattended.</li> </ul>
If inhaled	<ul> <li>If breathed in, move person into fresh air.</li> <li>If unconscious, place in recovery position and seek medical advice.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of skin contact	<ul> <li>Remove contaminated clothing. If irritation develops, get medical attention.</li> <li>If on skin, rinse well with water.</li> <li>First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.</li> <li>Wash contaminated clothing before re-use.</li> </ul>
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses.

Page: 3

Version: 1.5



Revision Date: 10/25/2017

Print Date: 4/3/2018 SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

**SAFETY DATA SHEET** 

804751

	Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed :	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms : and effects, both acute and delayed	Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
	Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) May cause an allergic skin reaction.
Notes to physician :	No hazards which require special first aid measures.

# **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media		Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting		Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	•	carbon dioxide and carbon monoxide Hydrocarbons



Page: 4

SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 4/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.5
804751	

# Specific extinguishing methods : Product is compatible with standard fire-fighting agents. Further information : Standard procedure for chemical fires. Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	se personal protective equipment. ersons not wearing protective equipment s om area of spill until clean-up has been co	
Environmental precautions	revent product from entering drains. revent further leakage or spillage if safe to	do so.
Methods and materials for containment and cleaning up	oak up with inert absorbent material (e.g. s tid binder, universal binder, sawdust). eep in suitable, closed containers for dispo	-
Other information	omply with all applicable federal, state, and	l local regulations.

# SECTION 7. HANDLING AND STORAGE

Advice on safe handlir	<ul> <li>Do not breathe vapours/dust. Do not smoke.</li> <li>Persons susceptible to skin sensitisation problems or asthma allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Container hazardous when empty.</li> <li>Avoid exposure - obtain special instructions before use.</li> <li>Avoid contact with skin and eyes.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>For personal protection see section 8.</li> <li>Dispose of rinse water in accordance with local and national regulations.</li> </ul>	,
Conditions for safe sto	e : Keep container tightly closed in a dry and well-ventilated	



# SAFETY DATA SHEET Revision Date: 10/25/2017 Print Date: 4/3/2018 Print Date: 4/3/2018 SDS Number: 000000149117 SDS Number: 000000149117 Valvoline™ CVT Full Synthetic Continuously Variable Version: 1.5 Transmission Fluid 804751

place.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

#### Hazardous components without workplace control parameters

Components	CAS-No.
Acetamide, 2-hydroxy-, N,N-	866259-61-2
dicoco alkyl derivs.	
C14-C18 alpha-olefin epoxide,	
reaction products with boric	
acid	

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### Personal protective equipment

Hand protection Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection	:	Wear as appropriate: Impervious clothing Safety shoes



SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 4/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.5
804751	

		Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures	:	Wash hands before breaks and at the end of workday.

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: clear
Odour	: characteristic
Odour Threshold	: No data available
рН	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 219.99 °F / > 104.44 °C Calculated Flash Point
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
	No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8436 g/cm3 (25 °C)
Solubility(ies) Water solubility	: immiscible



SAFETY DATA SHEETRevision Date: 10/25/2017Print Date: 4/3/2018Print Date: 4/3/2018SDS Number: 000000149117SDS Number: 000000149117Valvoline™ CVT Full Synthetic Continuously Variable<br/>Transmission FluidVersion: 1.5804751S05 Number: 00000149117

Page: 7

Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: 33.9 mm2/s (40 °C)
Oxidizing properties	: No data available

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons

# **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure	: Inhalation Skin contact Eye Contact Ingestion
Acute toxicity Not classified based on availab <u>Components:</u> HYDROTREATED LIGHT PAR Acute oral toxicity	
Acute inhalation toxicity	: LC50 (Rat): > 5.58 mg/l Exposure time: 4 h

Version: 1.5



Revision Date: 10/25/2017

Print Date: 4/3/2018 SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

# 804751

Test atmosphere: dust/mist Assessment: Not classified as acutely toxic by inhalation under GHS. Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

# Skin corrosion/irritation

SAFETY DATA SHEET

Not classified based on available information.

Remarks: May cause skin irritation in susceptible persons.

## Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: Species: Rabbit Result: No skin irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid: Result: No skin irritation

# Serious eye damage/eye irritation

Not classified based on available information. **Product:** Remarks: Unlikely to cause eye irritation or injury.

#### Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: Species: Rabbit Result: No eye irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid: Result: No eye irritation

# Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information. Components: HYDROTREATED LIGHT PARAFFINIC DISTILLATE: Test Type: Buehler Test Species: Guinea pig Assessment: Does not cause skin sensitisation.

Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.: Assessment: May cause sensitisation by skin contact. Result: May cause sensitisation by skin contact.

C14-C18 alpha-olefin epoxide, reaction products with boric acid:



SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 4/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.5
804751	

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. Reproductive toxicity Not classified based on available information. STOT - single exposure Not classified based on available information. STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information. <u>Product:</u> No aspiration toxicity classification Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: May be fatal if swallowed and enters airways.

# Further information

Product: Remarks: No data available

Carcinogenicity: IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

# SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.
Components:	



SAFETY DATA SHEET	Revision Date: 10/25/201
	Print Date: 4/3/201
	SDS Number: 00000014911
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.
804751	

HYDROTREATED LIGHT PAF Toxicity to fish	<ul> <li>RAFFINIC DISTILLATE:</li> <li>LL50 (Pimephales promelas (fathead minnow)): &gt; 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility</li> </ul>	
Toxicity to daphnia and other aquatic invertebrates	<ul> <li>EL50 (Daphnia magna (Water flea)): &gt; 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202</li> </ul>	
Toxicity to algae	<ul> <li>NOEL (Pseudokirchneriella subcapitata (green algae)): &gt;= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201</li> </ul>	
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l Exposure time: 14 d	
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	<ul> <li>NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211</li> </ul>	
Persistence and degradability <u>Components:</u>		
HYDROTREATED LIGHT PAF Biodegradability	RAFFINIC DISTILLATE: : Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B	
No data available Bioaccumulative potential <u>Components:</u> No data available <b>Mobility in soil</b> <u>Components:</u> No data available Other adverse effects No data available <u>Product:</u>		
Additional ecological	: No data available	



SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 4/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.5
804751	

information

# Components:

# **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods	
General advice	<ul> <li>Do not dispose of waste into sewer.</li> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Send to a licensed waste management company.</li> </ul>
	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	<ul> <li>Empty remaining contents.</li> <li>Dispose of as unused product.</li> <li>Empty containers should be taken to an approved waste handling site for recycling or disposal.</li> <li>Do not re-use empty containers.</li> </ul>

# **SECTION 14. TRANSPORT INFORMATION**

# International transport regulations

## REGULATION

RECOLATION					
ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

# U.S. DOT - ROAD

Not dangerous goods

#### CFR\_RAIL\_C

Not dangerous goods

# U.S. DOT - INLAND WATERWAYS

Not dangerous goods

# TDG\_ROAD\_C

Not dangerous goods

# TDG\_RAIL\_C

Not dangerous goods



SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 4/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.5
804751	

# TDG\_INWT\_C

Not dangerous goods

## INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

# INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

## INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

#### MX\_DG

Not dangerous goods

# \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15. REGULATORY INFORMATION**

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity This material does not contain any components with a CERCLA RQ. SARA 304 Extremely Hazardous Substances Reportable Quantity This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	Acute Health Hazard
SARA 313	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65	This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.



SAFETY DATA SHEET	Revision Date: 10/25/20
	Print Date: 4/3/20
	SDS Number: 0000001491
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1
804751	

The components of this pro DSL	duct are reported in the following inventories: : All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TSCA	: On TSCA Inventory


## Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

# **SECTION 16. OTHER INFORMATION**

#### Further information

Revision Date: 10/25/2017



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

# Full text of H-Statements

H317 May cause an allergic skin reaction.



SAFETY DATA SHEETRevision Date: 10/25/2017Print Date: 4/3/2018Print Date: 4/3/2018Valvoline™ CVT Full Synthetic Continuously Variable<br/>Transmission FluidVersion: 1.5804751S05 Number: 00000149117

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation

Page: 15



SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 4/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid	Version: 1.5
804751	

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association NIOSH : National Institute for Occupational Safety and Health OSHA : Occupational Safety and Health Administration PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System