

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV632

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**Product identifier**

Trade name : Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease

™ Trademark, Valvoline or its subsidiaries, registered in
various countries**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	50.00

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV632

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	50.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	9.9999
MOLYBDENUM DISULFIDE	1317-33-5	Not a hazardous substance or mixture.	2.4999

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
 If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
 Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV632

appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 Aldehydes
 Ketones
 Nitrogen oxides (NOx)
 Sulphur oxides

Specific extinguishing methods :
 Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV632

emergency procedures

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	ST ESL	1,000 µg/m3	TX ESL
		AN ESL	100 µg/m3	TX ESL
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	PEL	5 mg/m3 particulate	CAL PEL
		TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3	ACGIH

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 VV632

		TWA	Inhalable fraction 5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
MOLYBDENUM DISULFIDE	1317-33-5	TWA	15 mg/m3 total dust (Molybdenum)	OSHA Z-1
		TWA	10 mg/m3 Inhalable fraction (Molybdenum)	ACGIH
		TWA	3 mg/m3 Respirable fraction (Molybdenum)	ACGIH
		TWA	10 mg/m3 Total dust (Molybdenum)	OSHA P0
		PEL	10 mg/m3 Total dust (Molybdenum)	CAL PEL
		PEL	3 mg/m3 respirable dust fraction (Molybdenum)	CAL PEL

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
 Safety shoes
 Wear resistant gloves (consult your safety equipment supplier).

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV632

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Physical state : liquid

Colour : grey

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 640 °F / 338 °C

Flash point : 500 °F / 260 °C

Evaporation rate :
No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure :
No data available

Relative vapour density :
No data available

Relative density : No data available

Density : 0.94 g/cm³ (20 °C)

Solubility(ies)
Water solubility : negligible

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV632

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Auto-ignition temperature : > 315 °C

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous
reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition
products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): 6,477 mg/kg
Method: Acute toxicity estimate

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

 Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 VV632

Acute dermal toxicity : LD50 (Rabbit): 169,492 mg/kg
 Method: Acute toxicity estimate

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Remarks: Information given is based on data obtained from
 similar substances.

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: Not classified as acutely toxic by inhalation
 under GHS.
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: No adverse effect has been observed in acute
 dermal toxicity tests.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Acute oral toxicity : LD50 (Rat): > 5 g/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: Not classified as acutely toxic by inhalation
 under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: Not classified as acutely toxic by dermal
 absorption under GHS.
 Remarks: No mortality observed at this dose.

MOLYBDENUM DISULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.82 mg/l

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV632

Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute
inhalation toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species: Rabbit

Result: No skin irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species: Rabbit

Result: No skin irritation

MOLYBDENUM DISULFIDE:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species: Rabbit

Result: Slight, transient irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species: Rabbit

Result: Slight, transient irritation

MOLYBDENUM DISULFIDE:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
™ Trademark, Valvoline or its subsidiaries, registered in various countries
VV632

Method: OECD Test Guideline 406

Distillates (petroleum), solvent-dewaxed heavy paraffinic:
Test Type: Buehler Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

Germ cell mutagenicity
Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic:
No aspiration toxicity classification

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 VV632

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity**Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Scud (Gammarus pulex)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: semi-static test
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 VV632

Test Type: static test
 Test substance: WAF

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: WAF
 Method: OECD Test Guideline 211

Persistence and degradability**Components:****RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B
 Remarks: Information given is based on data obtained from similar substances.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:
 Biodegradability : Result: Inherently biodegradable.
 Method: OECD Test Guideline 301F



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV632

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:
 Biodegradability : Result: Inherently biodegradable.
 Biodegradation: 31 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

No data available
Bioaccumulative potential
Components:
 No data available
Mobility in soil
Components:
 No data available
Other adverse effects
 No data available
Product:
 Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.
 Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
™ Trademark, Valvoline or its subsidiaries, registered in various countries
VV632

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 4/5/2018

SDS Number: R0076416

Version: 1.2

Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV632

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/19/2017

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

		Page: 16
SAFETY DATA SHEET		Revision Date: 05/19/2017
		Print Date: 4/5/2018
		SDS Number: R0076416
Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV632		Version: 1.2

Combustible Liquid Class IIIB

Full text of H-Statements


Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity

	Page: 17
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 4/5/2018
	SDS Number: R0076416
Valvoline™ Ford-Lincoln-Mercury Multi-Purpose Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV632	Version: 1.2

TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System