

VALVOLINE™ SYNPOWER™ GREASE

Valvoline SynPower Grease is an excellent heavy-duty and multi-purpose automotive and industrial extreme pressure grease. It consists of a lithium complex thickener in synthetic base oil and is fortified with molybdenum disulfide and other quality additives. It provides protection from high loads and may be used over a wide temperature range.

Valvoline SynPower Grease is recommended for use in disc brake wheel bearings, all-purpose chassis lubrication, suspension systems, universal joints, steering linkage, and constant velocity joint applications.

Character: Molybdenum Disulfide, Rust and Oxidation Inhibited, Extreme Pressure Fortified

Approvals/Performance Levels

NLGI GC/LB, MACK GC-G

Typical Properties

NLGI Grade	2
Thickener Type	Lithium Complex
Color and Texture	Gray-Black / Buttery
ASTM Worked Penetration @ 77° F	275
ASTM Dropping Pt, °F	500 min.
ASTM D-1743 Rust Test	Pass
Weld Pt., kg	315
Load Wear Index, kg	60 min.
Vis @ 100°C (cSt)	12.0
Viscosity Index	135
Pour Point °C	-20
Timken OK Load, lbs	60 min.

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:
3/16/18

Author's Initials:
KD