

Make: Subaru

Model: 2015+ Outback

Applications: Rally Light Bar

PACKAGE CONTENTS				TOOLS
QTY		QTY		Flat Head Screwdriver 1/2" Socket/Wrench 9/16" Socket/Wrench Sharp Cutting Tool
1	Rally Light Bar	2	3/8" - 16 x 1.75" Hex Bolt	
2	Upper Bracket	2	3/8" - 16 x 2.5" Hex Bolt	
1	Lower Brace	4	3/8" - 16 Hex Nut	
6	5/16" Bolt Plate	8	3/8" Flat Washer	
6	5/16" Flat Washer USS	4	3/8" Lock Washer	
6	5/16" Lock Washer	2	3/4" Nylon Spacer	
6	5/16"-18 Hex Nut			

## INSTALLATION INSTRUCTIONS



Remove the front bumper cover and the foam piece in front of the bumper beam.

1



Insert (4) 5/16" Bolt Plates into the holes shown. Slide the Bolt Plates towards the center of the vehicle.

2



Attach (2) Upper Brackets to the bumper beam. Fasten with (1) 5/16" Flat Washer, Lock Washer, and Hex Nut on each Bolt Plate.

3



Insert (2) 5/16" Bolt Plates into the outer holes on the lower radiator support. Hold up the brace to verify fitment.

4



Attach the brace with (1) 5/16" Flat Washer and (1) Lock Washer per side.

5



Carefully reattach the bumper cover with the Upper Brackets through the grill as shown.

6



Attach the Light Bar as shown with (1) 3/8" x 1.75" Hex Bolt, (1) Flat Washer, (1) 3/4" Nylon Spacer, (1) Flat Washer, (1) Lock Washer, and (1) Hex Nut per side.

7



Attach the Light Bar to the Lower Brace with (1) 3/8" x 2.5" Hex Bolt, (2) Flat Washers, (1) Lock Washer, and (1) Hex Nut.

8



Cut the splash guard as shown by the tape.

9



Cut the splash guard by following the outer crease until the bar clears.

10