



PREPARING: Clean filter prior to oiling. Gently tap the filter to remove excess dirt. Lightly brush off surface dirt with soft bristle brush. Agitate element in ½" of hot water and laundry detergent, dishwashing soap, or an industrial cleaner (NONFLAMMABLE). DO NOT USE GAS OR FLAMMABLE LIQUIDS.


SOAKING: (Fig. A)
Spray the filter media with the Volant air filter cleaning agent until thoroughly soaked. Let the filter soak for approximately 10 minutes.



RINSING: (Fig. B)
Using low pressure from a tap or hose, rinse the element from the inside out until the water flows clear. DO NOT USE HIGH PRESSURE NOSELS NOR HOSES. Air dry naturally or lay the filter in front of a fan using a low setting. DO NOT USE HEAT NOR HIGH PRESSURE AIR AS IT CAN DAMAGE THE MEDIA.



OILING: (Fig. C)
Using Volant's special formula air filter oil, check to see if the filter media is completely dry. Start by placing a small bead of oil from the squeeze bottle on top of each filter pleat. Let is set for 20 minutes. This process allows the oil to wick throughout the filter media. If light spots appear spot touch those areas. NEVER USE A VOLANT FILTER WITHOUT OIL.



STEP 1 OF 2

FILTER CLEANER AIR FILTER CLEANING AGENT



NOTE: Sunlight deteriorates the oil. If the filter is exposed to sunlight for extended periods of time it will be necessary to re-oil the filter periodically.

**DO NOT USE COMPRESSED AIR
DO NOT USE OPEN FLAME
DO NOT USE HOT AIR DRYERS
DO NOT USE GASOLINE OR OTHER
CAUSTIC CLEANING SOLUTIONS.**

CAUTION:
Avoid contact with skin, eyes and mucous membranes.

FIRST AID TREATMENT:
Eye Contact:
Immediately flush with water for 15 minutes. If irritation persists call a physician.

Inhalation:
Remove to fresh air. If breathing is difficult, get medical attention.

Ingestion:
Do not induce vomiting. Immediately call a physician, poison control center or hospital treatment department.

KEEP OUT OF REACH