



Safety Data Sheet

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System Revision 7

Date of Revision: None

Revision: 0

Section 1 - Chemical Product and Company Identification

1.1 Product Name: Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS

1.2 Synonym: Blend

1.2 VP Racing Fuels, Inc.

1.3 Recommended Use: Light or Heavy-Duty Axles and Heavy Duty Non-Synchronized Manual Transmissions and Limited Slip Differentials calling for a Full Synthetic GL-5LS Gear Oil

1.4 RESTRICTIONS on USE Applications That Do Not Require a Full Synthetic SAE GL-5LS Gear Oil

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Hazard Categories

Eye Irritation

Category 2A

Skin Irritation

Category 2

Reproductive Toxicity

Category 2

Specific Target Organs toxicity repeated exposure

Category 2

Harmful to Aquatic Life with Long Lasting Effects

Category 3

2.2 Signal Word: Warning

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System Revision 7



Health

Irritant

2.3 Pictograms:

2.4 Hazard Statements

PHYSICAL HAZARDS:

None

HEALTH HAZARDS

H315: Causes skin irritation
H317: May cause an allergic skin reaction
H319: Causes serious eye irritation
H361: Suspected of damaging fertility or the unborn child
H373: May cause damage to organs through prolonged or repeated exposure

ENVIRONMENTAL HAZARDS:

H412: Harmful to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children
P202: Do not handle until all safety precautions have been read and understood
P260: Do not breathe mist
P264: Wash hands through after handling
P270: Do not eat, drink or smoke when using this product
P280: Wear protective gloves, clothing, and eye protection

RESPONSE STATEMENTS:

P303+P361+353: IF ON SKIN Take off immediately all contaminated clothing, rinse skin with water
P305+P351: IF IN EYES rinse cautiously with water for at least 15 minutes. If present, remove contact lenses if easy to do so
P308+P313: If exposed or concerned, get medical attention
P313+P332: If skin or eye irritation persists get medical attention
H314: Get medical attention if you feel unwell
P370: In case of fire use foam, carbon dioxide, dry chemical to extinguish fire
P376: Stop leaks if safe to do so

STORAGE STATEMENTS:

P405: Store lock up

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System Revision 7

DISPOSAL STATEMENTS:

P501: Dispose of content and/or container in accordance with local, regional, national or international regulations

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS Repeated exposure may cause skin dryness or cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Classification
N/A	N/A	Hi Performance Full Synthetic gear oil with Additives	100 %	None

3.2 Blend Contains

Chemical Names	CAS#	EC/List#	Classification
1-Octene Homopolymer, Hydrogenated	70693-43-5	None	Not Classified
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1	Asp.Tox.1 H304
Phenylmethane	108-88-3	203-625-9	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Repr. 2 H361, STOT RE 2 H373
Mineral oil	64742-53-6	265-156-6	Carc. 1B H350
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	270-128-1	Aquatic Chronic 3 H412
Benzothiazole-2-thiol	149-30-4	205-736-8	Skin Sens.1 H317, Aquatic acute H400, Aquatic Chronic H410

3.3 Trade Secret Provision and Chemical Concentration Disclosure: In accordance with OSHA and GHS Regulations we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and are applicable to the hazards as identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can cause irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause irritation, defatting and drying of the skin.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System Revision 7

4.3 Ingestion: Causes headache, gastrointestinal pain, nausea, and. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 After first aid, get appropriate paramedic, or community medical support. The severity of outcome following an exposure may be more related to the time between exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

4.6 Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment we will immediately disclose the specific chemical identity. We will require a written statement of need and confidentiality agreement, in accordance with OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards: Use water to cool containers exposed to fire.

5.2 Hazardous Combustion Products: Avoid fumes of burning product.

5.3 Extinguishing Media: Carbon dioxide, dry chemical, foam

5.4 Fire Fighting Equipment/Instructions: Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Evacuate area. Only trained and properly protected personnel must be involved in clean-up operations. Keep upwind of spill. Ventilate area of leak or spill.

6.2 Spills: Avoid direct contact with material. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin or clothing. Keep container tightly closed. Avoid inhalation.

7.2 Storage Requirements: Store in a tightly closed container locked up.

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS
 Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
 Conforms to The United Nations Regulation Globally Harmonized System Revision 7

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Hi Performance Full Synthetic gear oil with Additives	5mg/m3 TWA	5mg/m3 TWA

8.2

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation are preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse.
 Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Viton is a Registered Trademark of The DuPont Company

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System Revision 7

8.6 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Dark

Odor: Aromatic Hydrocarbon

Vapor Pressure: 45 mmHg@21°C

Vapor Density (Air=1): Not Available

Specific Gravity (H₂O=1,): Not Available

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not Applicable

Evaporation rate: Not Available

Partition coefficient octanol/water: 2 to 6

Water Solubility: Insoluble

Flash Point: 561°F, 293.8 °C close cup

Boiling Point: 600-1200 °F, 315.5-648-8 °C

Freezing/Melting Point: Not Available

Viscosity: Not Available

Auto ignition Temperature: Not Available

LEL: Not Applicable

UEL: Not Applicable

Viscosity: Kinematic 143 cm²/s@104°F,40°C

Auto ignition Temperature: Not Available

Decomposition temperature: Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage

10.2 Polymerization: Hazardous polymerization has not been reported

10.3 Chemical Incompatibilities: Strong oxidizing agents

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide

10.5 Conditions to Avoid: Avoid heat, sparks open flames and other ignition sources

Section 11- Toxicological Information

11.1 Product Name	Results	Species	Dose	Exposure
Hi Performance Full Synthetic gear oil with Additives	Oral LD50	Rat	>2000 mg/kg	None Listed

11.2 Route of Entry: Ingestion, Absorption, Skin and/or Eye Contact

11.3 Aspiration Hazard: European Chemical Agency Data Base shows that components of this product may be fatal if swallowed and enters airways.

NOTE: **Viscosity shows this blend not to be** fatal if swallowed and enters airways

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System Revision 7

11.4 Acute Toxicity: harmful if swallowed. OECD Guideline Test results found in the European Chemical Agency Data Base shows that no components of this product to be Harmful Oral Toxicity.

11.5 Mutagenicity: OECD Guideline Test results found in the European Chemical Agency Data Base show no components of this product to cause genetic defects.

11.6 Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause skin irritation. Repeated exposure may cause skin dryness or cracking.

11.7 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause eye irritation.

11.8 Reproductive toxicity: OECD Guideline Test results found in the European Chemical Agency Data Base show components of this product to cause damage to fertility or the unborn child.

11.9 Specific Target Organ Toxicity (Single Exposure): None shown

11.10 Target Organ Toxicity (Repeated Exposure): Contains material which may cause damage to the following organs: Eyes, skin and respiratory system.

11.11 Signs and Symptoms: Effects may include: Headache, Dizziness, Drowsiness. Symptoms may be delayed.

11.12 Carcinogenicity: OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause cancer, however by test contains <3% DMSO extract per IP346 and is not considered to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Hi Performance Full Synthetic gear oil with Additives	Not listed	Not listed	Not listed	Not listed

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Hi Performance Full Synthetic gear oil with Additives	Expected to be Harmful to aquatic organisms. May cause long-term adverse effects in the environment		

Toxicity: OECD Guideline Test results found in the European Chemical Agency Data Base show components of this product to cause long-term toxicity to aquatic life.

12.2 Mobility: Floats on water

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS
Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System Revision 7

12.5 Other adverse effects: Inconclusive technical data.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! Container should be completely emptied prior to discard. Container with residues should be considered to be hazardous wastes. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 DOT Transport Information

Not Regulated

ID No.:

Shipping Name:

Hazard Class:

Packing Group:

Label:

Placard:

Marking:

14.2 IMDG Transport Information

Not Regulated

ID No.:

Shipping Name:

Hazard Class:

Packing Group:

Label:

Placard:

Marking:

14.3 UN Dangerous Goods Transport Information

Not Regulated

ID No.:

Shipping Name:

Hazard Class:

Packing Group:

Label:

Placard:

Marking

Section 15 - Regulatory Information

15.1 US Regulations

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System Revision 7

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

TRI Reporting SARA 313: Phenylmethane

CERCLA Hazardous Substances and corresponding RQs: Phenylmethane 1000pounds

SARA Community Right-to-Know Program: All components of this blend

Clean Water Act: Phenylmethane

Clean Air Act: None

OSHA: All ingredients are regulated by 1910.1200

State Regulations

California prop. 65:



WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov.”

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements

New Jersey All components of this product are on the New Jersey inventory or are exempt from Inventory requirements

Pennsylvania: All components of this product) are on the Pennsylvania Inventory or are exempt from Inventory requirements.

15.2 International Regulations:

Australian Inventory of Chemical Substance: All components of this product are on the Inventory or are exempt from Inventory requirements.

National Existing Chemical Inventory in Taiwan: All components of this product are on the Inventory or are exempt from Inventory requirements.

Philippine Inventory of Chemicals and Chemical Substances All components of this product are on the Inventory or are exempt from Inventory requirements.

China Existing Chemical Inventory: All components of this product are on the Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information

Hi Performance Full Synthetic API GL-5 Gear Oil SAE 75W-140LS

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Conforms to The United Nations Regulation Globally Harmonized System Revision 7

provided above is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMpendium data base of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller on Line, European Chemical Agency Data Base Chinese Data Base Classification Labeling of Hazardous Chemicals, Australia Data Base for GHS Chemical Classification and MSDS and SDS of chemicals in this mixture.