

ATV SYNTHETIC ROPE EXTENSION 50' PN 69069

Your safety, and the safety of others, is very important. To help you make informed decisions about safety, we have provided installation and operating instructions and other information on labels and in this guide. This information alerts you to potential hazards that could hurt you or others. It is not possible to warn you about all potential hazards associated with this product, you must use your own good judgment.

CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE. READ AND UNDERSTAND ALL SAFETY PRECAUTIONS AND OPERATING INSTRUCTIONS BEFORE INSTALLING AND OPERATING THIS PRODUCT.

This guide identifies potential hazards and has important safety messages that help you and others avoid personal injury or death. WARNING and CAUTION are signal words that identify the level of hazard. These signal words mean:

A WARNING signals a hazard that could cause serious injury or death, if you do not follow recommendations.

CAUTION signals a hazard that may cause minor to moderate injury, if you do not follow recommendations. This guide uses NOTICE to call attention to important mechanical information, and Note: to emphasize general information worthy of special attention

GENERAL SAFETY PRECAUTIONS:	
🖄 WARNING!	CAUTION!
Moving Parts Entaglement Hazard	Moving Parts Entaglement Hazard
Failure to observe these instructions could lead to severe injury or death	Failure to observe these instructions could lead to minor injury or property damage
Always keep hands clear of rope, hook loop, hook and fairlead opening during operation when spooling in or out. Never use as an overhead hoist or to suspend a load. Never use to lift or move persons.	Always stand clear of rope and load during operation.Always be certain the anchor you select will withstand, load and the strap or will not slip.Always use a choker chain, wire choker rope, or tree trunk protector on the anchor.Never hook rope back on to itself, or tie knots in rope. This permanently damages the rope.Never exceed the working load limit of 4000 lbs, or shock load the rope.Never use rope if worn, damaged, abused, overloaded, or improperly maintained.Never use rope over a rough surface with out chafe protection.Never bend rope around unprotected sharp corners.Never use rope to secure a load during transport. Always inspect the rope before each use to ensure the rope is in proper working condition.