



# INSTALLATION INSTRUCTIONS NEOPRENE COVER KIT

## GENERAL SAFETY PRECAUTIONS

Your safety, and the safety of others, is very important. To help you make informed decisions about safety, we have provided installation and operating instructions and other information on labels and in this guide. This information alerts you to potential hazards that could hurt you or others. It is not possible to warn you about all potential hazards associated with this product, you must use your own good judgment.

**CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE. READ AND UNDERSTAND ALL SAFETY PRECAUTIONS AND OPERATING INSTRUCTIONS BEFORE INSTALLING AND OPERATING THIS PRODUCT.**

This guide identifies potential hazards and has important safety messages that help you and others avoid personal injury or death. **WARNING** and **CAUTION** are signal words that identify the level of hazard. These signal words mean:

▲ **WARNING** signals a hazard that could cause serious injury or death, if you do not follow recommendations. ▲ **CAUTION** signals a hazard that may cause minor to moderate injury, if you do not follow recommendations.

This guide uses **NOTICE** to call attention to important mechanical information, and **Note:** to emphasize general information worthy of special attention.

## **NOTICE**

### Equipment Damage

- Always use appropriate and adequate care when fitting cover into place.
- Always insure cover will remain secure while driving vehicle.
- Always check winch cover once per month for fading.
- Always use UV protectant spray every 2 to 6 months to minimize or prevent fading of Neoprene fabric.

Read installation and operating instructions thoroughly.

# INSTALLATION INSTRUCTIONS

## INSTALLATION:

1. Ensure logo is facing forward then slide right side of cover down over winch until bottom right flap of cover can slide under gear housing.
2. Pull left end of cover to stretch Neoprene and slide left end of cover down until bottom of cover can slide under motor end.
3. Adjust as needed to straighten cover on winch and align it to fit properly and smooth out any wrinkles.
8. For high sun environments (California, Texas, Arizona, Nevada, etc) repeat steps 2 thru 7 every 2 or 3 months. For milder climates repeat every 5 to 6 months.
9. Check your cover monthly for any signs of fading by folding the front edge of cover up so you can compare the inside fabric color with the outside fabric color. If fading has occurred, perform steps 2 thru 7 immediately.

## REMOVAL:

1. Grasp right bottom flap of cover and pull to the right until it can slide off of the gear housing.
2. Pull right end upward until it clears the gear housing.
3. Pull cover up and to the left to slide it out from under the motor and pull cover off of winch.

## CARE INSTRUCTIONS:

1. This Neoprene cover requires frequent maintenance to reduce or prevent fading caused by Ultraviolet (UV) radiation.
2. Remove cover from winch.
3. If cover is dirty, clean it with mild soap and water then let it air dry indoors out of the sun.
4. Once dry, lay cover flat and spray cover with 303 UV Protectant Spray making sure to cover it completely.
5. Turn cover over and repeat step 4.
6. Let protectant remain on cover for 5 minutes then blot cover to remove excess protectant and dry neoprene.
7. Reinstall cover on winch.

**CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE. READ AND UNDERSTAND ALL SAFETY PRECAUTIONS AND OPERATING INSTRUCTIONS BEFORE INSTALLING AND OPERATING THIS PRODUCT.**

