

1558 – FLAT CORNER LICENSE PLATE MOUNT TJ/LJ

INSTALLATION SHEET

Kit Contents:

Item	Qty	Item	Qty
License Plate Mount	1	Square Nylon Nut	4
Rubber Edge Trim	2.5 ft.	#14 x 1" Self-Tapping Screws	4

- 1. Remove your license plate from the factory license plate mount. This will expose the four fasteners that hold the mount to the jeep body.
- Remove the 4 fasteners that hold the factory license plate mount to the jeep tub. ***MAKE SURE TO KEEP TRACK OF THIS HARDWARE BECAUSE YOU WILL BE RE-USING IT TO ATTACH YOUR NEW LICENSE PLATE MOUNT.***
- 3. Prepare the <u>Warrior Products License Plate</u> mount by inserting the 4 Square Nylon Nuts into the corresponding square holes as shown. **Fig. 1**







4. Place the protective rubber edge trim along the edges of the mount that will be in contact with the jeep. Work the trim around the corners as shown and trim off any excess as necessary.

Fig. 2

- Attach the Warrior license plate mount to the jeep using the 4 factory fasteners that were saved from step2. Align the license plate mount to your satisfaction before final tightening. Fig.3
- Complete the installation by attaching your license plate (and license plate frame if applicable) to the license plate mount. Use the included #14 Self-Tapping screws and screw them into the corresponding Square Nylon Nuts.
- 7. Installation complete.



THANK YOU FOR PURCHASING WARRIOR PRODUCTS

QUALITY • INTEGRITY • INNOVATION • SERVICE