

Recommended Air Filter Cleaning Intervals: 3000 Miles

US Patent# US 7,263,961B2

Part #'s Secret Weapon: 301-148
Application: 2004-05 ACURA TSX 4CYL

Parts List: 1 x Weapon*R Intake pipe. /1 x Weapon*R Air Filter /1 x 15mm x 16" Hose /1 x 10mm x 12" hose 2x 2.75"-3" /1 x Intake System Bracket kit / 3 x 3" clamp / 2 x 1" Clamps

- 1 Remove the PVC emissions box from OEM tube, Disconnect the plastic EVAP hardline from OEM intake pipe.
- 2 Loosen the OEM airbox and rubber intake tube, disconnect the MAF sensor harness from OEM airbox
- 3 Place the 2.75" 3" coupler onto the throttle body and secure with the OEM clamp.
- 4 Place Weapon*R Intake Tube into the 3" end of the coupler and secure with clamp.
- 5 Install the 8mm hose onto the 8mm port on intake pipe and the plastic EVAP hardline on the engine .
- 6 Insert the Weapon*R filter into the intake pipe, secure with clamp.
- 7 Note: Dragon / Secret Weapon Filter Option : Disregard installation on Hyper filter.
- 8 Install 2.75 " 3" coupler onto Dragon or Secret Weapon air filter, secure with supplied clamp.
- 9 Install filter assembly onto the end of Weapon*R intake pipe, secure with OEM clamp.
- 10 Install U-shaped part of intake system bracket under the clamp on air filter.
- 11 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 12 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 13 Secure with washer and nut included in bracket kit.
- 14 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 15 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 16 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE!**Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.



