



Recommended [Air Filter](#) Cleaning Intervals: 3000 Miles.

Part #'s **Secret Weapon Intake : 301-160**

US Patent# US 7,263,961B2

Application : **2007-2008 Acura RDX TURBO**

Parts List : 1 x Weapon*R Intake pipe. / 1 x Weapon*R Air Filter / 1 x 3"-3" Coupler / 2 x 2.5"-3" Coupler

- 1 Loosen the OEM airbox and rubber intake tube, disconnect the MAF sensor harness from OEM airbox
- 2 Carefully remove the MAF sensor from the OEM airbox, remove the rubber intake tube and OEM airbox
- 3 Place the 2.5"- 3" coupler onto the throttle body and secure with the OEM clamp.
- 4 Place Weapon*R Intake Tube into the 3" end of the coupler and secure with clamp.
- 5 Install the MAF sensor onto the Weapon-R intake pipe, secure with OEM screws, reconnect harness.
- 6 **Note: Secret Weapon Filter Option :**
- 7 Install 3" coupler onto Secret Weapon air filter, secure with supplied clamp.
- 8 Install filter assembly onto the end of Weapon*R intake pipe, secure with OEM clamp.
- 9 Install U-shaped part of intake system bracket under the clamp on air filter.
- 10 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 11 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 12 Secure with washer and nut included in bracket kit.
- 13 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 14 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 15 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

NOTE: Only some early models used a MAF sensor. Disregard MAF info if not applicable to your vehicle.

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !**
Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

