



CARB PENDING

Recommended Air Filter Cleaning Intervals: 3000 Miles.
US Patent# US 7,263,961B2

Part # 's **Secret Weapon: 302-130**

Application : **1999-03 Mazda Protégé 1.6L**

Parts List : 1 x Intake pipe. / 1 x Air Filter / 1 x 10mm x 12" Hose / 1 x 2.5"-2.5" coupler
1 x 2.5"- 3" Coupler / 1 x Intake Bracket kit / 4 x 3" Clamp

- 1 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 2 Remove the PCV hoses from OEM intake and engine.
- 4 Unplug and remove the MAF sensor from the OEM air intake hose.
- 5 Remove the OEM rubber intake tube, remove the OEM air cleaner box by pulling upwards.
- 6 Wipe the throttlebody clean of any grease, install the 2.5" coupler onto throttlebody, secure with OEM clamp.
- 7 Insert Weapon*R intake pipe into the 2.5" coupler, secure with clamp.
- 8 Measure the OEM PVC hoses, replace with supplied 10mm hoses, install from PVC ports to intake pipe.
- 10 Stretch the 2.5-3" coupler onto end of intake pipe, secure with clamp.
- 11 Insert MAF into the WR intake pipe and secure down with supplied screws, connect MAF harness.
- 12 Install the Weapon*R Hyper filter onto AFM sensor.

Note: Secret Weapon Filter Option :

- 13 Install 2.5"-3" coupler onto the Secret Weapon air filter, secure with supplied clamp.
- 14 Install filter assembly onto the intake pipe, secure with OEM clamp.
- 15 Install U-shaped part of intake system bracket under the clamp on air filter.
- 16 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 17 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 18 Secure with washer and nut included in bracket kit.
- 19 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 20 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 21 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !**
Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

