

Part #'s SECRET WEAPON: 304-129

Application: 2005-06 Sentra 1.8S

Parts List: 1 x Intake pipe. /1 x Air Filter / 2 x 3" coupler / 1 x 15mm x 12" hose

1 x 2.5"- 3" Coupler / 1 x Intake Bracket kit / 3 x 3" Clamp / 1 x AFM-NS Adapter plate

- 1 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 2 Remove the PCV 15mm Air recirculator hoses from OEM intake.
- 4 Unplug and remove the MAF sensor from the air intake system.
- 5 Remove the OEM rubber intake tube, remove the OEM air cleaner box by pulling upwards.
- 6 Install the 2.5-3" coupler onto throttlebody, secure with OEM clamp.
- 7 Insert Weapon\*R intake pipe into the coupler, secure with clamp.
- 8 Install the supplied 15mm hose onto the intake pipe and to the PCV port on valve cover
- 10 Install the 3" coupler onto end of intake pipe, secure with clamp.
- 11 Insert MAF into the 3" coupler, secure with clamp, connect MAF harness.
- 12 Line up the holes on MAF to the AFM-NS adapter plate, secure with nuts and bolts in kit.
- 14 Install 3" coupler onto Secret Weapon air filter, secure with supplied clamp. Install filter assembly onto the AFM adapter plate, secure with OEM clamp.
- 15 Install U-shaped part of intake system bracket under the clamp on air filter.
- 16 Install the rubber mounting grommet to the closest hole to the Weapon\*R air filter.
- 17 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 18 Secure with washer and nut included in bracket kit.
- 19 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 20 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 21 Place Weapon\*R CARB Sticker on a visible place in engine compartment. ( If Applicable )

## WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Returned Products may be subject to a 25% restocking charge. INSTALLED PRODUCTS ARE NON-REFUNDABLE!

Note: Report any defective or missing parts to the authorized Weapon\*R dealer you purchased this product from. Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.





Recommended Air Filter Cleaning Intervals: 3000 Miles.

US Patent# US 7,263,961B2



