

Part #'s Secret Weapon Intake: 305-146

Application: 2004-2006 LEXUS RX330

Parts List: 1 x Weapon*R Intake pipe. /1 x Weapon*R Air Filter 3" /1 x 10mm x 8" Hose 4 x 4mm hose, 1 x 2.5"-3" coupler, 2 x 3"-3" coupler1 x Intake System Bracket kit

Note: Additional Parts needed when you have a Dragon Filter, 1 x 3" Coupler / 2 x 3" Clamps

- 1 Disconnect the MAF sensor harness, carefully remove MAF sensor from OEM airbox,
- 2 Remove air recirculator valve & hose from OEM intake and engine.
- 3 Remove bolts securing OEM air cleaner box, remove OEM air intake box.
- 4 Clamp 2.5"-3" coupler onto throttle body.
- 5 Bolt MAF sensor into pipe using screw provided.
- 6 Reconnect al Ithe 4mm lines to WR pipe.
- 7 Install the 10mm hose onto the air recirculator valve and onto the Weapon*R intake pipe.
- 8 Install the Weapon*R Hyper filter onto the end of the intake pipe.
- 9 Install MAF sensor into Weapon*R intake pipe, reconnect MAF sensor harness.
- 10 Install the 3" coupler onto Secret Weapon air filter, secure with supplied clamp.
- 11 Install filter assembly onto the end of Weapon*R intake pipe, secure with OEM clamp.
- 12 Install U-shaped part of intake system bracket under the clamp on air filter.
- 13 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 14 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 15 Secure with washer and nut included in bracket kit.
- 16 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 17 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 18 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE!**Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.





Recommended Air Filter Cleaning Intervals: 3000 Miles.

US Patent# US 7,263,961B2