



CARB PENDING

Recommended Air Filter Cleaning Intervals: 3000 Miles.

Part # 's **Secret Weapon: 306-115**

US Patent# US 7,263,961B2

Application : **2001-04 Subaru OUTBACK H6**

Parts List : 1 x Weapon*R Intake pipe. / 1 x Weapon*R Air Filter 3"/ 2 x 2.75"-3" coupler
1 x Intake System Bracket kit / 3 x 3" Clamp

- 1 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 2 Remove the OEM rubber intake tube, remove the OEM air cleaner box by pulling upwards.
- 3 Install the 3" coupler onto the air resonator box, secure with OEM clamp.
- 4 Insert Weapon*R intake pipe into the 2.75" coupler, secure with clamp.
- 5 Install the Weapon*R Hyper filter onto the end of the intake pipe.
Note: Dragon / Secret Weapon Filter Option : Disregard installation on Hyper filter.
- 6 Install 2.75"- 3" coupler onto Dragon or Secret Weapon air filter, secure with supplied clamp.
- 7 Install filter assembly onto the end of Weapon*R intake pipe, secure with OEM clamp.
- 8 Install U-shaped part of intake system bracket under the clamp on air filter.
- 9 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 10 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 11 Secure with washer and nut included in bracket kit.
- 12 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 13 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 14 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !**
Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

