

CARB PENDING

Recommended Air Filter Cleaning Intervals: 3000 Miles. US Patent# US 7,263,961B2

Application : 2010 Kia Soul 2.0L

Parts List : 2 x Weapon*R Intake pipe. /1 x Weapon*R Air Filter 3" / 1 x 10mm x 12" Hose / 2 x 3"-3" Coupler 1 x 2.75-3" Coupler / 1 x Intake System Bracket kit / 6 x 3" Clamp

- 1 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 2 Remove PCV hose from OEM intake and engine.

Part # 's SECRET WEAPON INTAKE #346-112-301

- 4 Remove the OEM rubber intake tube by unclamping the OEM clamps and pulling off OEM tube
- 5 Remove 2 x clips to front ram scoop
- 6 Remove the OEM air cleaner box by unclipping the top and pulling upwards and off.
- 7 Remove bottom half of airbox by unbolting 3 x 10mm bolts holding it ot the vehicle, and lift straight out
- 8 Wipe the throttlebody clean of any grease, install the 2.75"-3" coupler onto throttlebody, secure with clamp.
- 9 Insert Weapon*R intake pipe into the 3" side of coupler, secure with clamp.
- 10 Install the 3""-3" coupler onto end of intake pipe, secure with clamp.
- 11 Measure the OEM PVC hose, replace with supplied 10mm hose, install from PCV port to intake pipe. Note: Secret Weapon Filter Option :
- 12 Install 3"-3" couple ronto SW filter and clamp down, then install onto Cold air piece and clamp down
- 13 Route the installed filter and pipe under the inner fender liner, up to the upper intake pipe and clamp down
- 14 Install U-shaped part of intake system bracket under the clamp on air filter.
- 15 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 16 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 17 Secure with washer and nut included in bracket kit.
- 18 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 19 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 20 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !** Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from. Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

