



Recommended Air Filter Cleaning Intervals: 3000 Miles.

Part # 's **Hyper Intake : 901-146 / Dragon Intake : 801-146**

Application : **2004-2007 ACURA TL V6 3.2L**

Part # 's **Hyper Intake : 901-147 / Dragon Intake : 801-147**

Application : **2003-2007 HONDA ACCORD 3.0L V6**

Parts List : 1 x Weapon*R Intake pipe. / 1 x Weapon*R [Air Filter](#) 3" / 1 x 10mm x 2" hose
1 x 3" Coupler / 1 x Intake System Bracket kit / 1 x 3" Clamp

Note: Additional Parts needed when you have a Dragon Filter, 1 x 3" Coupler / 2 x 3" Clamps

- 1 Remove the PVC emissions hardline from OEM intake tube,
- 2 Loosen the OEM airbox and rubber intake tube, remove OEM airbox and OEM rubber intake tube.
- 3 Place the 3" coupler onto the throttle body and secure with the OEM clamp.
- 4 Place Weapon*R Intake Tube into the 3" coupler and secure with clamp.
- 5 Install the 10mm hose onto the 10mm port on intake pipe and the PVC hardline on the engine .
- 6 Insert the Weapon*R filter into the intake pipe, secure with clamp.

Note: Dragon / Secret Weapon Filter Option : Disregard installation on Hyper filter.

- 7 Install 3" coupler onto Dragon or Secret Weapon air filter, secure with supplied clamp.
- 8 Install filter assembly onto the end of Weapon*R intake pipe, secure with OEM clamp.
- 9 Install U-shaped part of intake system bracket under the clamp on air filter.
- 10 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 11 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 12 Secure with washer and nut included in bracket kit.
- 13 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 14 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 15 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !**
Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

