



CARB # D-489-1

Recommended Air Filter Cleaning Intervals: 3000 Miles.

Part # 's **Hyper Intake : 905-124 / Dragon Intake : 805-124**

Application : **1999-03 Lexus RX300 / 2001-04 Toyota Highlander V6**
(2004 Highlander CARB restricted)

Parts List : 1 x Weapon*R Intake pipe. / 1 x Weapon*R [Air Filter](#) 3" / 1 x 10mm x 8" Hose
1 x Intake System Bracket kit / 1 x plastic "T" fitting

Note: Additional Parts needed when you have a Dragon Filter, 1 x 3" Coupler / 2 x 3" Clamps

- 1 Disconnect the MAF sensor harness, carefully remove MAF sensor from OEM airbox,
 - 2 Remove air recirculator valve & hose from OEM intake and engine.
 - 3 Remove bolts securing OEM air cleaner box, remove OEM air intake box.
 - 4 **NOTE:** On highlander models disconnect the 3 x 4mm lines from the OEM airbox, and put aside.
 - 5 Insert Weapon*R intake pipe into the OEM rubber intake tube, secure with clamp.
 - 6 Install the 10mm hose onto the air recirculator valve and onto the Weapon*R intake pipe.
 - 7 Install the Weapon*R Hyper filter onto the end of the intake pipe.
 - 8 Install MAF sensor into Weapon*R intake pipe, reconnect MAF sensor harness.
 - 9 **NOTE:** Highlander models use 1/4" "T" fitting and reconnect the 3 x 4mm lines from step 4, to "T" fitting ([PIC BELOW](#))
- Note: Dragon / Secret Weapon Filter Option : Disregard installation on Hyper filter.**
- 8 Install the 3" coupler onto Dragon or Secret Weapon air filter, secure with supplied clamp.
 - 9 Install filter assembly onto the end of Weapon*R intake pipe, secure with OEM clamp.
 - 10 Install U-shaped part of intake system bracket under the clamp on air filter.
 - 11 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
 - 12 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
 - 13 Secure with washer and nut included in bracket kit.
 - 14 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
 - 15 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
 - 16 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !**
Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

