



CARB PENDING

Recommended Air Filter Cleaning Intervals: 3000 Miles.

Part # 's Dragon intake Intake : 807-185

Application : 2000-2004 Chrysler 300M 3.5L V6

Parts List : 2 x Weapon*R Intake pipe. / 1 x Weapon*R Air Filter 3" / 1 x 15mm x 12" Hose / 3 x 3"-3" Coupler / 1 x Intake System Bracket kit / 6 x 3" Clamp/ 1x black rubber grommet

- 1 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 2 Remove PCV hose from OEM intake and engine.
- 3 Remove the OEM rubber intake tube, remove the OEM air cleaner box by pulling upwards.
- 4 Remove the OEM airbox attached to the stock rubber elbow near the throttle body.
- 5 Leave the OEM rubber 90 degree tube attached to the throttle body.
- 6 Wipe the OEM rubber 90 degree tube clean of any grease
- 7 Insert 1st Weapon*R intake pipe into the OEM 90 degree elbow, secure with clamp.
- 8 Install 3"-3" coupler onto end of 1st intake tube, clamp down.
- 9 Install the second WR intake tube into 3"-3" coupler and secure down with clamp
- 10 Measure the OEM PVC hose, replace with supplied 15mm hose, install from PVC port to intake pipe.

Note: Dragon intake Filter Option

- 12 Install the 3"-3" coupler onto the end of the second WR intake pipe, secure with supplied clamp.
- 13 Install filter assembly onto the 3"-3" coupler, secure with clamp.
- 14 Install U-shaped part of intake system bracket under the clamp on air filter.
- 15 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 16 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 17 Secure with washer and nut included in bracket kit.
- 18 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 19 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 20 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !**
Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.
Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

