



Part # 's 959-111-126

Application : 2003- 2008 Mazda 6 2.0L and 2.3L

Parts List : 1 X [ENGINE DAMPER](#) / 1 X STRUT TOWER MOUNTING BRACKET
1 X L-BRACKET / 1 X MOUNTING HARDWARE KIT/ 2 x 10mm bolts and nuts

- 1 Jack up the front of the vehicle, place jack stands under vehicle.
- 2 Place a piece of wood on top of the jack, slowly jack up the engine from the oilpan.
- 3 Raise up the jack till it is snug against the oilpan.
- 4 Remove the 2 nuts on the left side engine mount.
- 5 Remove the Main bolt to the top engine mount and Lift up on the upper part of the mount
- 6 Install the L-Bracket onto the engine mount over the studs and reinstall the OEM top mount
- 7 Install the engine damper kit on the L-bracket, secure with supplied mounting hardware.
- 8 Loosen A/C hose mounting bracket bolt. Reposition AC bracket as shown. AC bracket can be bent downward for additional damper clearance.
- 9 Place strut tower mounting bracket onto passenger side strut tower bolts.
- 10 Install the other end of engine damper onto strut tower mounting bracket, secure with supplied hardware.
- 11 Adjust length of engine damper to desired length.
- 12 Lower jack from Oilpan slowly.
- 13 Jack up the front of the vehicle, remove jack stands and slowly lower vehicle.
- 14 Installation is complete.

