

**SEATBACK
PROTECTOR**

WeatherTech®



Installation Instructions

Universal Seatback Protector

SBP003CH – Black
SBP003GY – Grey
SBP003TN – Tan



STEP 1

Hold the Universal Seatback Protector to the back of the desired seat. Pull the top straps around the headrest and connect the buckles.

NOTE

If seat is equipped with adjustable headrest, raise headrest and attach around support(s). Adjust strap to desired length.

STEP 2

Pull the lower straps around the lower portion of the backrest and connect the buckles. Adjust strap to the desired length.

NOTE

Pay close attention to the strap routing so they do not interfere with any seat airbag, latches, or any other mechanisms.

Installation Complete.

! IMPORTANT

DO NOT INSTALL THIS PRODUCT IN A MANNER THAT WILL INTERFERE WITH ANY VEHICLE OCCUPANT SAFETY SYSTEMS. THIS PRODUCT IS NOT DESIGNED TO RESTRAIN PETS, OCCUPANTS OR CARGO IN THE EVENT OF A COLLISION.

CLEANING INSTRUCTIONS:

1. Using a large commercial washer without agitator, wash the Seatback Protector using $\frac{1}{4}$ cup of a gentle detergent, without bleach, in cold water. Do not pour detergent directly onto the Seatback Protector.
2. Rinse the Seatback Protector twice (2X) to remove all of the detergent.
3. Hang and allow to air dry.

SPOT-CLEANING:

1. Mix one ounce of a gentle detergent, without bleach, per quart of warm water.
2. Spray or sponge onto the Seatback Protector.
3. Rinse with plain water (until no suds) and allow to air dry.