

WeatherTech®

SillProtector



Alcohol Pads



Masking Tape*

*Not included



SillProtector



Install Video

NOTE: Please make sure vehicle surface and SillProtector parts are at or above 60° F (16° C) for proper tape adhesion.

Installation Instructions



1 Wash the door sills of your vehicle and completely dry with a clean cloth. It is important that the door sills remain completely dry and free of any dirt and debris throughout the installation process.



2 Place SillProtector on door sill for a trial fit. Make sure you are using the character lines of your door sill to match with the SillProtector.



3 With the SillProtector held in place on your door sill, outline the edges of it on your sill with masking tape.



4 Once you outline it, remove the SillProtector and use the included alcohol pads to deep clean the contact area, then let dry completely.



5 Prepare for installation by peeling back the adhesive liner from each section on the underside of the SillProtector. Fold the adhesive liners back far enough to create pull tabs.



6 Carefully place the SillProtector back into position within the outlined masking tape on your door sill. Remove the masking tape after SillProtector is in place.



7 Remove the adhesive liner. Grasp the exposed portion of the adhesive liner and pull gently with one hand while applying light, even pressure to the SillProtector with your opposite hand. Repeat this step until all adhesive liner has been removed.



8 Using the palm of your hand, apply additional pressure from the center out, pressing down firmly along all the adhesive lined edges to ensure proper adhesion.



9 Congratulations on installing your WeatherTech SillProtectors! Your SillProtectors will be fully bonded within 24 hours. Do not wash your vehicle for 72 hours after installation.

LET'S TALK

800-441-6287

For warranty information, please visit www.WeatherTech.com/warranty



Made in USA

67ST001 © 2023 MacNeil IP LLC