


Installation Instructions

Thank you for purchasing the WeatherTech® Seat Protector for Bucket Seats. Please read this installation guide to thoroughly familiarize yourself with the steps to install the Seat Protector into your vehicle.



1.
Unroll cover. Place seat bottom portion grippy side down and fold seat back portion over onto bottom portion. Ensure the half with straps is on top.



2.
Insert foam attachment between seat cushion and seat back.




3.
Unfold top half upwards to cover the seat back and secure the strap around the headrest. Buckle the strap and tighten.



4.
Attach hook & loop strap behind the lower part of the seat back.



5.
Attach hook & loop straps behind seat back.



6.
Do not cover seatbelt buckle.



7.
Finish installation by pulling the bottom portion of the Seat Protector around the seat bottom, draping it from the seat to the floor.



8.
Please check your seat for full range of motion forward/backward – particularly on vehicles with automatically retracting seats.

HELPFUL HINT:

Move front row seats forward for extra room during installation.

When installing “Semi-Custom” products, additional adjustments may be necessary to achieve desired fit.

CLEANING INSTRUCTIONS:

1. Using a large commercial washer without agitator, wash the Seat Protector using 1/4 cup of a gentle detergent, without bleach, in cold water. Do not pour detergent directly onto the Seat Protector.

2. Rinse the Seat Protector twice (2X) to remove all of the detergent.

3. Hang and allow to air dry

SPOT-CLEANING:

1. Mix one ounce of a gentle detergent, without bleach, per quart of warm water.

2. Spray or sponge onto the Seat Protector.

3. Rinse with plain water (until no suds) and allow to air dry.

! NOTE:

IF YOUR VEHICLE HAS SIDE IMPACT AIRBAGS THAT ARE IMBEDDED WITHIN THE SEAT, PLEASE DO NOT INSTALL SEAT PROTECTOR IF ANY OF THE MOUNTING STRAPS OR ANY PART OF THE SEAT PROTECTOR WILL INTERFERE WITH SIDE IMPACT AIRBAG DEPLOYMENT.

For additional information, please refer to your vehicle owners manual, or consult your local dealer.



Please look for this tag