
WESTIN LED LIGHT BARS

B-FORCE

BLACK FACE WITH DIAMOND PLATE PATTERN / SINGLE ROW / POWER OUTPUT: 30 - 250 WATTS



- 5W Cree LED chips
- 6063 extruded aluminum housing with die-cast ends
- Dust and moisture resistant lens
- GORE® pressure equalizing vent
- Raw Lumens: 2,980 24,900
- · Includes mounting hardware and pigtail connector
- · Limited lifetime warranty

· Available in Flood or Combo beam





PIGTAIL CONNECTOR


— BEAM PATTERNS —













MODEL	A	В	C	D
09-12211-6	7.6 in.	3.4 in.	1.9 in.	3.7 in.
09-12211-10	11.6 in.	3.4 in.	1.9 in.	3.7 in.
09-12211-20	21.4 in.	3.4 in.	1.9 in.	3.7 in.
09-12211-30	31.3 in.	3.4 in.	1.9 in.	3.7 in.
09-12211-40	41.1 in.	3.4 in.	1.9 in.	3.7 in.
09-12211-50	50.9 in.	3.4 in.	1.9 in.	3.7 in.

PART NO.	POWER OUTPUT	BEAM Type	LEDS	FACE Size	AMP DRAW 12V	RAW Lumens	BEAM Distance	OPERATING Voltage
09-12211-6F	30	Flood	6 x 5w Cree	6"	1.65	2980	299	9-30V
09-12211-10C	50	Combo	10 x 5w Cree	10"	3.3	4980	384	9-30V
09-12211-20C	100	Combo	20 x 5w Cree	20"	6.5	9960	525	9-30V
09-12211-30C	150	Combo	30 x 5w Cree	30"	9.5	14940	635	9-30V
09-12211-40C	200	Combo	40 x 5w Cree	40"	12.8	19920	738	9-30V
09-12211-50C	250	Combo	50 x 5w Cree	50"	15.7	24900	807	9-30V

B-FORCE

EP BLACK FACE WITH DIAMOND PLATE PATTERN / DOUBLE ROW / POWER OUTPUT: 12 - 300 WATTS

- Face sizes available in 2", 4", 6", 10", 12, 20", 30", 40" and 50" lengths
- 3W Cree LED chips
- 6063 extruded aluminum housing with die-cast ends
- Dust and moisture resistant lens
- Raw Lumens: 1,080 27,000
- · Includes mounting hardware and pigtail connector
- Limited lifetime warranty
- · Available in Flood and Combo beam










6" OR 10" HDX FLUSH Mount Led Kit Available See Page 10



B-FORCE Double LED Light Bar - Combo Beam







— BEAM PATTERNS —

COMBO

MODEL	А	В	C	D
09-12212-4	4.1 in.	3.4 in.	3.1 in.	4.8 in.
09-12212-8	6.1 in.	3.4 in.	3.1 in.	4.8 in.
09-12212-12	8.1 in.	3.4 in.	3.1 in.	4.8 in.
09-12212-20	12.1 in.	3.4 in.	3.1 in.	4.8 in.
09-12212-24	14.1 in.	3.4 in.	3.1 in.	4.8 in.
09-12212-40	22.2 in.	3.4 in.	3.1 in.	4.8 in.
09-12212-60	32.2 in.	3.4 in.	3.1 in.	4.8 in.
09-12212-80	42.2 in.	3.4 in.	3.1 in.	4.8 in.
09-12212-100	52.2 in.	3.4 in.	3.1 in.	4.8 in.

PART NO.	POWER OUTPUT	BEAM Type	LEDS	FACE SIZE	AMP DRAW 12V	RAW Lumens	BEAM Distance	OPERATING Voltage
09-12212-4F	12	Flood	4 x 3w Cree	2"	0.8	1080	104	9V-30V
09-12212-8F	24	Flood	8 x 3w Cree	4"	1.6	2160	123	9V-30V
09-12212-12C	36	Combo	12 x 3w Cree	6"	2.0	3240	326	9V-30V
09-12212-20C	60	Combo	20 x 3w Cree	10"	4.2	5400	525	9V-30V
09-12212-24C	72	Combo	24 x 3w Cree	12"	8.2	6480	610	9V-30V
09-12212-40C	120	Combo	40 x 3w Cree	20"	12	10800	849	9V-30V
09-12212-60C	180	Combo	60 x 3w Cree	30"	15.9	16200	909	9V-30V
09-12212-80C	240	Combo	80 x 3w Cree	40"	16.6	21600	1103	9V-30V
09-12212-100C	300	Combo	100 x 3w Cree	50"	18.8	27000	1154	9V-30V



Check out a selection of off-road lights offered in our online store.