


INSTALLATION INSTRUCTIONS

APPLICATION: 1999-UP FORD F-250/350/450/550HD SUPERDUTY REGULAR CAB

AUTOMOTIVE PRODUCTS, INC.

STEP BAR ASSEMBLIES 25-1320 25-1325



| ITEM | QTY | CONTENTS | TOOL |
|------|-----|-------------------------------------|---------------|
| 1 | 2 | STEP BAR, PASSENGER AND DRIVER | 3/4" SOCKET |
| 2 | 2 | FRONT DRIVER/REAR PASSENGER BRACKET | 1/2" SOCKET |
| 3 | 2 | FRONT PASSENGER/REAR DRIVER BRACKET | 1/2" WRENCH |
| 4 | 4 | 1/2-13 X 2.00" HEX HEAD BOLT | TORQUE WRENCH |
| 5 | 4 | 1/2" FLAT WASHER | RATCHET |
| 6 | 4 | 1/2" LOCK WASHER | |
| 7 | 12 | 5/16-18 X 1.25" HEX HEAD BOLT | |
| 8 | 20 | 5/16" FLAT WASHER | |
| 9 | 12 | 5/16" LOCK WASHER | |
| 10 | 8 | 5/16-18 HEX NUT | |
| 11 | 4 | 5/16-18 CLIP NUT | |

- STEP 1. Remove contents from box and check for damage. Verify all parts are present. Read instructions completely before beginning.
- STEP 2. Insert nut clips into rocker panel as shown. **SEE FIGURES 1 AND 2.**
- STEP 3. Install front and rear brackets as shown. Hand tighten. **SEE FIGURES 3 AND 4.**
- STEP 4. Attach step bar to brackets. Make sure step bar and brackets are properly aligned. Tighten and torque 1/2" fasteners to 65 Ft. Lbs; 5/16" fasteners to 30 Ft. Lbs. **SEE FIGURE 5.**

FINISH PROTECTION

Westin products have a high quality finish that must be cared for like any other exposed finish on the vehicle. Protect the finish with a non-abrasive automotive wax, (e.g. Pure Carnauba) on a regular basis. The use of any soap, polish or wax that contains an abrasive is detrimental, as the compounds scratch the finish and open it to corrosion.

