



INSTALLATION INSTRUCTIONS


APPLICATION: 2005-08 NISSAN FRONTIER KING CAB/CREW CAB 2005-08 NISSAN XTERRA

AUTOMOTIVE PRODUCTS, INC.

STEP BAR ASSEMBLIES				
25-2730	25-2735			
25-2750	25-2755	26-2750		
25-3470	25-3475	26-3470		







ITEM	QTY	CONTENTS	TOOLS
1,2 3 4 5 6 7 8	2 3 12 12 12 12	STEP BAR, PASSENGER (1) AND DRIVER (2) MOUNT FRONT PASSENGER/REAR DRIVER MOUNT FRONT DRIVER/ REAR PASSENGER 3/8-16 X 1.00" BUTTON HEAD BOLT 3/8" INTERNAL TOOTH LOCK WASHER M8 FLAT WASHER M8-1.25 HEX REVERSIBLE LOCK NUT	13MM SOCKET 13MM WRENCH 7/32" HEX WRENCH RATCHET TORQUE WRENCH

- STEP 1. Remove contents from box and check for damage. Verify all parts are present. Read instructions completely before beginning.
- STEP 2. Determine bracket locations for passenger front/driver rear and driver front/passenger rear brackets. **SEE FIGURES 1 AND 2.**
- STEP 3. Locate passenger side mounting locations on vehicle. Attach mount brackets to rocker panel. Leave loose. **SEE FIGURE 2.**
- STEP 4. Attach passenger side step bar to cradles with the Westin logo facing outward as shown. Assemble with 3/8" fasteners. Leave loose. **SEE FIGURES 2 AND 3.** The step pad closest to the bend goes to the rear of the vehicle.
- STEP 5. Make sure step bar and brackets are properly aligned with vehicle and tighten fasteners. Recommended torque values are 22 FT.LBS. for 8mm fasteners and 19 FT.LBS. for 3/8" fasteners.
- STEP 6. Repeat installation for opposite side.

FINISH PROTECTION

Westin products have a high quality finish that must be cared for like any other exposed finish on the vehicle. Protect the finish with a non-abrasive automotive wax, (e.g. Pure Carnauba) on a regular basis. The use of any soap, polish or wax that contains an abrasive is detrimental, as the compounds scratch the finish and open it to corrosion.

