# WÖHLER



# MODULAR POINT OF VIEW

Wohler VIS 400 Visual Inspection Modular System

**Professional Visual Inspection System** 









1.5" dia.

PAN/TILT COLOR
CAMERA HEAD

2" dia.
PAN/TILT COLOR
CAMERA HEAD















# Wohler VIS 400 Visual Inspection Modular System

A camera system that keeps you in the picture and sharpens your awareness

With the strap around your neck and the monitor in front of your chest, one hand guides the camera cable, the other precisely controls the camera head via the Wohler keypad. The new Wohler VIS 400 Visual Inspection System is designed for ease of use while doing either vertical inspections while standing on steep roofs.

Modular by design, it is possible to combine the Wohler VIS 400 Visual Inspection System with a variety of camera vipers, camera cables and camera heads. For instance, simply connect either the Wohler 2" dia or the 1 1/2" dia pan & tilt camera head to carry out a variety of inspections. Both of these cameras pan 360 and tilt 180 while offering the best possible lighting. After panning and tilting, the home function automatically aligns the angle of the 1 1/2" dia color camera to straight ahead with a simple push of a button.

View, speak and save

The Wohler VIS 400 will make a video recording of the inspected line run. When damage is discovered, begin the voice recording function to annotate the recording. As well as recording video, you may also take and save still photos at the press of a button.

Knowing where really matters

To be able to assess and specifically target repair work, we at Wohler have perfected the technique of precisely locating the camera head. The distance and the position of the head are displayed on the monitor. The top and bottom of the pipe are displayed on the monitor at all times, even if the camera is being guided up or down or if it is moving left or right. It is even possible to locate the 1 1/2" dia color camera head wirelessly – utilizing the new Wohler L 200 Locator.

### **ADVANTAGES**

- Perfect for either vertical or horizontal inspections
- Adjustable LED lighting
- Modular system to choose individual components to suit application requirements
- Compact and easy to use 3 lbs featherweight
- Includes carry strap and protective pouch with anti-glare protection

# Modular System Design

Put your camera system together to suit your requirements and wishes. Select your components from the list below and more:

#### Wohler VIS 400 Cable Reel Camera



#### Wohler VIS 400 Push rod Camera



Application examples with 2" dia camera head

#### Camera Heads



2" dia color camera head, pan- & tiltable



1 1/2" dia color camera head, pan- & tiltable



1" dia color camera head for smaller pipe diameters

## Detachable Wohler Supplementary light for 2" dia color camera head



### **Overview of Functions**

#### Digital meter counter

For precision length orientation in conjunction with the Wohler camera viper and cable reel

#### Pan & Tilt Camera Head 2" dia

Includes selectable LED illumination Pan & Tilt controlled via arrow keys



#### Lighting

Adjust the brightness of the camera head lighting via the dimming function

#### **Eyelets**

To secure wrist and shoulder straps

#### Video output

To transmit the video signal to an external monitor

#### USB port

For data transfer

#### SD card

Recorded data is stored on a 4 GB SD card

#### Shift

Activates the key functions which are represented by the green symbols on the keypad

#### **Battery status**

2 hours of rechargeable battery operation for lasting mobility

#### Playback

Starts or ends a video or photo playback

#### Menu

A variety of user-definable settings

### Photo, video and voice recording

Capture images and voice annotations of what you see

#### Delete

Delete an image or video, switch the camera on/off or reset the meter counter to zero

#### **X** Applications

Analyze damage and visually inspect:

- · Flue gas systems, chimneys
- · Building drains, house connections
- · Ventilation systems

#### ☼ Functionality

- Modular system components are modular by design to support extensive expansion options
- Pan & Tilt color camera heads with integrated power lighting easily negotiate bends in the line
- Digital meter counter with a resolution of 0.10 ft, displayed on the monitor (with Wohler camera viper or cable reel)
- · Mini USB port for data transmissions

#### Data management

Integrated video output – simply record and store photos, videos and voice annotations on a 4 GB SD card for documentation and archiving purposes for you and your customers.

#### **TECHNICAL DATA**

#### Monitor

TFT display	7" / 16:9 format
Video out	FBAS signal
Power supply	12 V NiMH rechargeable battery, 2.000 mAh
Battery operating time	2 h (battery status in display)
Distance measurement	Digital meter counter in conjunction with the camera viper
	and cable reel
Storage	4 GB SD card (2.5 h recording capacity)
Interface	Mini USB port
Operating temperature	32104 °F
Storage temperature	4122 °F

#### **Dimensions housing**

without pouch......8" x 8" x 2"

#### **Dimensions housing**

with pouch	.9"	Χ	9"	Х	3"
------------	-----	---	----	---	----

Weight ...... Without pouch 3 lbs; with pouch 4 lbs

Connection, stand ...... Standard



Monitor anti-glare protection ensures optimum viewing even in the glare of the sun.



Professionally equipped with camera viper for inspecting underground pipelines.



No unnecessary ballast on the roof – helps you keep your balance in the most difficult of conditions.

### Kit and Accessories

Sets Wohler VIS 400	Qty Accessories Qt
Wohler VIS 400 Standard Kit Comes with: Wohler VIS 400 color TFT monitor 7" with 4 GB SD card and power supply, protection bag with glare protector and shoulder belt, pan&tilt camera head 2" dia, camera cable 100 ft., power supply, plastic case  P/N 4133	Plastic domes Wohler VIS 400 Camera Head pack of 5 pieces  P/N 7075  Wohler Replacement Glass Dome for pan & tilt camera heads Wohler VIS 2000 PRO / VIS 400 color and
Wohler VIS 400 Push Rod Camera	b/w P/N 7802
Comes with: Wohler VIS 400 color monitor NTSC with leather bag and shoulder belt, pan & tilt color camera head 2" dia, stabilization sleeve for color camera head, 4 GB SD card, camera roller guide with protection cage, camera viper with 100 ft. push rod 0.3" dia, aluminium case XXL  P/N 4152	Wohler Camera Holder faces down P/N 3720 Wohler VIS Guidance Set 110
Wohler VIS 400 Cable Reel Camera Comes with: Wohler VIS 400 color monitor NTSC with leather bag and shoulder belt, cable reel with integrated distance measurement	for pan and tilt camera head: camera roller cage with protection cage and stabilization sleeve with star holder  P/N 3881
(resolution 2" shown on screen), connection cable for reel and monitor, 4 GB SD card, pan&tilt color camera head 2" dia with camera holder, replacement glass dome for camera head, camera cable 100 ft. with metric marking, aluminium case XXL	Wohler Stabilisation sleeve aluminium for 2" dia pan and tilt camera heads; for use with camera cable: head can be pushed upwards with GRP Rods
P/N 4153	P/N 22182
Wohler VIS 400 Monitor only Comes with: Wohler VIS 400 color monitor NTSC in heavy duty carrying case, protective bag with glare shield and shoulder belt, 4 GB SD card, power supply P/N 4781	Wohler Telescopic Tube with flexible gooseneck for camera heads Wohler VIS 400 / VIS 2000 PRO and Wohler miniature camera heads, length of the telescopic tube 0.9 1.6 m plus gooseneck 0.3 m. The flex and stay gooseneck remains in a bent position allowing for easy inspection  P/N 7005
	17111000
	Wohler VIS Cleaning Set with plastic case, for approx. 50 applications 1 liter desinfection spray, 50 cleaning tissues, 100 disposable gloves size XL (powder free), 6.76 ounce lubricant, plastic case  P/N 4725
	Wohler VIS Cleaning Set Refill
	for approx. 50 applications 1 liter desinfection spray, 50 cleaning tissues, 100 disposable gloves size XL (powder free), 6.76 ounce lubricant, in plastic bag
	P/N 4726
	Wohler Supplementary Light

for Wohler Camera Head, 2" dia Wohler Supplementary Light - detachable

P/N 4194





### **Wohler VIS 400 Video Inspection System**

Monitor		
FT display	7" / 16:9 format	
	FBAS signal	
Battery operating tim	e2 h (battery status in display)	
Distance measureme	ntDigital meter counter in conjunction	
	with the camera viper and cable reel	
Storage		
nterface	Mini USB port	
Operating temperatu	re32104 °F	
Storage temperature	4122 °F	
Dimensions housing		
vithout pouch	8" x 8" x 2"	
Dimensions housing		
vith pouch	9" x 9" x 3"	
Veight		
Connection, stand		