

ULTRA RADIATOR HOSE

ZIRUHR12, ZIRUHR24, ZIRUHR36, ZIRUHR48

DESCRIPTION OF UHR SERIES

DON'T COLLAPSE! Zirgo's UltraHose™ has a strong corrugated structure that will not collapse or crack like typical rubber radiator hoses. The UltraHose™ Stainless Steel Hose Kits are available in 4 lengths; 12", 24", 36", and 48" for 1-1/4", and 1-3/4" O.D. water necks. With this many sizes in one kit, the UltraHose™ is sure to fit almost any hot rod, street truck, muscle car, import or custom vehicle out there.

The UltraHose™ Stainless Steel Hose Kit contains one UltraHose™ Flexible Corrugated Hose, two polished billet aluminum smooth hose ends, four stainless steel hose clamps, and two 1-3/4" and 1-1/4" neoprene reducers, along with 2 each- 1-3/4" high strength sleeve adaptors. Also available in matching heater hoses.

Features of UHR Series

- Hose Length :: 12", 24", 36", 48"
- Fittings :: 2
- Maximum size: 1.75"
- Adapters OD:: Two 1.25", Two 1.75"
- Hose Diameter :: 2"
- Adjustable Hose :: Yes
- Adjustable Clamps :: Yes
- Stainless Steel Hose Clamps :: 4
- Neoprene Reducers and Sleeves Create Universal Fit for Any Engine Type
- Flexible Corrugated Stainless Steel Hose
- Easy Engine Dress Up
- Limited Lifetime Warranty

TO INSTALL

Simply verify length of hose needed and confirm size ID of hose ends.

To adjust length:

Remove any and all pieces connected to the hose itself.

Measure and mark the hose to the appropriate size.

Using a SHARP saw, work saw through material using minimal force, as not to bend or distort the hose material itself.

Finish edge with grinder/coarse sand paper.

Replace adaptors.

To change the size:

Simply remove the rubber sleeve appropriate for the size you would like.



Once all adjustments have been made, attach to components using bolts within adaptors, tightening each side equally. Do not overtighten, as this may cause an issue with your components inlet/outlet pipes.